

LED INTERNAL LOW PROFILE AMENITY LIGHT - WHITE



DATA SHEET

 **MADE IN
BRITAIN**



The BLE BD7 is a popular choice for amenity lighting with a modern low profile decorative design and a robust polycarbonate opal diffuser.

230V

LED

IP20


3 YEAR
GUARANTEE*

Stylish and modern design

Impact modified polycarbonate opal diffuser

Microwave sensor version available reducing energy consumption

Dimensions



Specification

| | |
|-----------------------------|---|
| Input Voltage: | 230V, 50Hz |
| Total Wattage: | 16W |
| Lamp Wattage: | 14W |
| Emergency Duration: | 3hrs |
| Mode of Operation: | Maintained / Non-maintained |
| Working Temperature: | 0°C - 40°C |
| Tested To: | BS EN 60598-2-22 BS EN 60598-1 |
| Material: | Metal housing and polycarbonate diffuser |

*Guarantee excludes all batteries which have a 12 month guarantee

Version 3. 09/2021



BLE LIGHTING AND POWER LTD
Unit 3, Drake Business Park
Drake House Crescent, Sheffield, S20 7HT

T: 01246 432325 F: 01246 432324
E: sales@blelighting.co.uk
www.blelighting.co.uk





Additional Information

- Healthy charge indicator
- Reduced power consumption
- Surface mounted
- High quality metal housing
- Impact modified polycarbonate opal diffuser
- Higher light output version available (2850lm)
- 3000K version available

EMERGENCY VERSION

- 24 hour recharge time
- 3.6V 3.0Ah NiCD Battery

| Code | Description | Dimensions (Ø x D mm) |
|----------------------|---|-----------------------|
| BD7/LED/M3/WO/TB | LED Internal Low Profile Amenity Light - White - 3hr Emergency | 425 x 110 |
| BD7/LED/M3/WO/MS/TB | LED Internal Low Profile Amenity Light - White - 3hr Emergency - Microwave Sensor | 425 x 110 |
| BD7/LED/230/WO/TB | LED Internal Low Profile Amenity Light - White - 230V Mains | 425 x 110 |
| BD7/LED/230/WO/MS/TB | LED Internal Low Profile Amenity Light - White - 230V Mains - Microwave Sensor | 425 x 110 |

| PRODUCT REFERENCE | MOUNTING HEIGHT (M) | TRANSVERSE TO WALL (M)  | | TRANSVERSE SPACING (M)  | | AXIAL TO WALL (M)  | | AXIAL SPACING (M)  | |
|-------------------|---------------------|---|-------|---|-------|--|-------|---|-------|
| | | 0.5 LUX | 1 LUX | 0.5 LUX | 1 LUX | 0.5 LUX | 1 LUX | 0.5 LUX | 1 LUX |
| BD7/LED/M3/WO/TB | 2.50 | 2.80 | 1.90 | 7.30 | 5.50 | 2.80 | 1.90 | 7.30 | 5.50 |
| | 4.00 | 2.50 | N/A | 7.70 | 4.90 | 2.50 | N/A | 7.70 | 4.90 |
| | 6.00 | N/A | N/A | 6.60 | N/A | N/A | N/A | 6.60 | N/A |